

RANGE COMPOSITION

The range consists of 6 fan assisted models of 600 litre refrigeration cabinets that offer excellent standards in terms of performance and efficiency. These models come in freezer version with a choice of materials (stainless steel or white painted steel) and are available with full doors.



726318

AU SERIES

600 LT DIGITAL FREEZERS **ZANUSSI** PROFESSIONAL

FUNCTIONAL AND CONSTRUCTION FEATURES

◆ Internal and external structure in stainless steel or white painted steel, external base, top and back in galvanized steel (stainless steel on

model RS06FX1F4). 150 mm high - adjustable feet.


| TECHNICAL DATA | | | | | | |
|--|---------------------|--------------------|---------------------|--------------------|---|---------------------|
| CHARACTERISTICS | MODELS | | | | | |
| | RS06FX1F4 726457 | RS06FX1F 726318 | RS06F41FS 728303 | RS06FW1F 726474 | RS06FX2H 726690 | RS06FX1FR 727104 |
| Operating temperature - min/max °C | -22/-15 | -22/-15 | -22/-15 | -22/-15 | -22/-15 | -22/-15 |
| Operating mode | Ventilated | Ventilated | Ventilated | Ventilated | Ventilated | Ventilated |
| Type of stainless steel | | | | | | |
| external | 304 AISI | 304 AISI | Stainless Steel | Prepainted Steel | Stainless Steel AISI 304 Scotch Brite | 304 AISI |
| internal | 304 AISI | 304 AISI | Stainless Steel | Stainless Steel | Stainless Steel AISI 304 Scotch Brite | 304 AISI |
| Gross capacity (D.I.N. 8952) - l. | 600 | 600 | 600 | 600 | 600 | 600 |
| Cooling unit | Built-In | Built-In | Built-In | Built-In | Built-In | Remote |
| External dimensions - mm | | | | | | |
| width | 720 | 720 | 720 | 720 | 720 | 720 |
| depth/with open doors | 788, 1440 | 788, 1440 | 788, 1440 | 788, 1440 | 788, 1450 | 788, 1440 |
| height | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 |
| Door hinges | Right Side | Right Side | Right Side | Right Side | Right Side | Right Side |
| N° and type of grids (included) | 3, GN 2/1 | 3, GN 2/1 | 3, GN 2/1 | 3, GN 2/1 | 4, GN 2/1 | 3, GN 2/1 |
| N° defrost in 24 hrs. | 4/30' | 4/30' | 4/30' | 4/30' | 4/30' | 4/30' |
| Refrigerant type | R404a | R404a | R404a | R404a | R404a | R404a |
| Refrigerant quantity - g. | 270 | 270 | 270 | 270 | 270 | 270 |
| Refrigeration power - W | 752 | 752 | 752 | 752 | 752 | 843 |
| Power - kW | | | | | | |
| installed-electric | 0.66 | 0.66 | 0.66 | 0.66 | 0.66 | 0.175 |
| Internal light | ● | | | | | |
| Noise level - dBA | 59.5 | 59.5 | 59.5 | 59.5 | 59.5 | |
| Net weight - kg. | 134 | 134 | 128 | 134 | 134 | 134 |
| Power supply - V, phases, Hz | 230 V, 1, 50 | 230 V, 1, 50 | 230 V, 1, 50 | 230 V, 1, 50 | 230 V, 1, 50 | 230 V, 1, 50 |
| INCLUDED ACCESSORIES | | | | | | |
| 2 S/S SIDE RUNNERS FOR 600-1300L REFRIG. | | | | | 4 | |
| 2/1 GN GREY "RILSAN" GRID | 3 | 3 | 3 | 3 | 4 | 3 |
| SET OF 2 S/S RUNNERS FOR 650/1400-L.REF. | 3 | 3 | 3 | 3 | | 3 |

- ◆ Digital control panel allowing the easy and precise setting and control of the internal temperature.
- ◆ Completely automatic defrosting and automatic evaporation of defrost water (304 AISI models), manual emptying of defrost water (Stainless steel models).
- ◆ High standards of hygiene and ease of cleaning are guaranteed by the rounded internal corners of the cabinet and easily removable runners and grids (without the use of tools).
- ◆ The refrigeration unit can operate in tropical climates (+43°C ambient temperature).
- ◆ Extremely quiet operation at 51 dBA.
- ◆ Excellent forced air cooling system that ensures the utmost uniformity of temperature in the cabinet and guarantees a perfect storage quality of the goods.
- ◆ High-density expanded polyurethane insulating foam, 60 mm in thickness, with cyclopentane injection, guarantees exceptional, long-term insulation and notable energy savings.
- ◆ The rational use of the internal space of the refrigerator guarantees a large storage area suitable to contain 2/1 GN grids.
- ◆ Reversible self-closing door, in positions less than 90°, with a stop at 95° and a maximum opening at 180°, equipped with a magnetic door seal to guarantee perfect closure. The pressed stainless steel recessed door handle without joints makes opening the cabinet extremely easy. All the doors are fitted as standard with locks and keys and a microswitch to switch off the fan when the door is opened.
- ◆ Stainless steel feet (plastic interior).
- ◆ A wide range of optional accessories are available.
- ◆ CFC and HCFC free.

| OPTIONAL ACCESSORIES | | | | | | |
|---|---------------------|--------------------|---------------------|--------------------|--------------------|---------------------|
| ACCESSORIES | MODELS | | | | | |
| | RS06FX1F4 726457 | RS06FX1F 726318 | RS06F41FS 728303 | RS06FW1F 726474 | RS06FX2H 726690 | RS06FX1FR 727104 |
| 2 S/S SIDE RUNNERS FOR 600-1300L REFRIG. | | | | | 880557 | |
| 2 WHEELS FOR REFRIGERATORS/REFRIG. TABLES | 880539 | 880539 | 880539 | 880539 | 880539 | 880539 |
| 2/1 GN AISI 304 S/S GRID | 881067 | 881067 | 881067 | | 881067 | 881067 |
| 2/1 GN GREY "RILSAN" GRID | 880720 | 880720 | 880720 | 880720 | 880720 | 880720 |
| ENERGY FREE ALARM DEVICE | | 881089 | 881089 | 881089 | 881089 | 881089 |
| KIT HACCP EKIS | 922166 | 922166 | 922166 | 922166 | 922166 | 922166 |
| KIT INTEGRATED HACCP-DIG. REFR. (IR33) | 880205 | 880205 | 880205 | 880205 | 880205 | 880205 |
| KIT TO FIT 11 PASTRY TRAYS (400X600 MM) | 881031 | 881031 | 881031 | 881031 | 881031 | 881031 |
| MEAT RAIL FOR 650-1400 L REFRIGERATORS | 881451 | | | | | |
| PRINTER FOR HACCP BASIC VERSION REFRIG. | 881457 | 881457 | 881457 | 881457 | 881457 | 881457 |
| REMOTE UNIT -24-15°C FOR 550/650 LT | | | | | | 881465 |
| SET OF 2 S/S RUNNERS FOR 650/1400-L.REF. | 881456 | 881456 | 881456 | 881456 | | 881456 |



www.zanussiprofessional.com




LEGEND

| | RS06FX1F4 726457 | RS06FX1F 726318 | RS06F41FS 728303 | RS06FW1F 726474 |
|----------------------------|---------------------|--------------------|---------------------|--------------------|
| EI - Electrical connection | 230 V, 1, 50 | 230 V, 1, 50 | 230 V, 1, 50 | 230 V, 1, 50 |



www.zanussiprofessional.com




LEGEND

| | |
|----------------------------|--------------------|
| | RS06FX2H 726690 |
| EI - Electrical connection | 230 V, 1, 50 |



www.zanussiprofessional.com



LEGEND

| | |
|-------------------------------------|-----------------------------|
| | RS06FX1FR 727104 |
| EI - Electrical connection | 230 V, 1, 50 |
| EO - Remote electrical connection | ● |
| M - Remote refrigeration connection | ● |



www.zanussiprofessional.com