

## MD1402X

Stainless Steel Multideck

## **Product features**

- Premium design
- Stainless steel exterior and interior
- Adjustable shelves with tilting function
- Temperature Class 3M1
- Shelf stopper for tilting is accessory
- LED interior light with switch
- Digital controller and temperature display
- Night blind / Curtain with soft release





Soft release night blind / curtain

Adjustable shelves with tilting function

## Open front multideck with stainless steel interior and exterior

The TEFCOLD MD-X range of open front multidecks finished in stainless is a great choice for shops, cafes, sandwich shops, butchers and convenience stores. Available in different widths between 685mm and 1885mm there is a size to suit most situations.

The unit is only 680mm deep and is ideal where there is limited floor space but you need to maximise refrigerated display area. With a base shelf and 4 adjustable shelves there is plenty of product storage space. Mirror finish stainless steel interior helps give a sense of space within the cabinet while bright white vertical LED lighting gives excellent illumination of the product (the MD1902X also has a horizontal LED light across the top).

The temperature range can be adjusted to suit your requirement including fresh meat, dairy or soft drinks or beer. Shelves can be angled between 2 and 20 degrees to give extra merchandising options (front shelf stops are required if shelves are angled). The unit comes fitted with rollers to enable the unit to be moved for cleaning, there is also and option for castors. The unit is also available in black.

Design and Material				
No. of Shelves	pcs	4		
Shelves No & Type		4 SS304 shelves, tilting		
Shelf Color		Stainless steel		
Feet / Legs		2 adjustable feet		
Castors		4 rollers		
Exterior Finish		Stainless steel		
Interior Finish		Stainles Steel		
Interior Light		LED		

Measures and Content				
Temperature Range	°C	-1 to +5		
Climate Class		3		
Gross / Net Weight	kg	210 / 188		
Gross / Net Volume	I	913 / 665		
Total Display Area	m²	1,6		

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic	
Refrigerant		R290	
Refrigerant Charge	g	135	
GWP		3	

Power and Consumption	
Energy Class	E
Energy Arrow	A A

Annual Energy Consumption	kWh/ye	ear 6971,5
EEI		63,6
Power		
Max Ambient		25°C at 60% RH
Input Power	W	920
Voltage / Frequency	V/Hz	220-240/50
Noise Level	db(A)	55

kWh/24h

Dimensions

Energy Consumption

Power and Consumption				
Internal Dimension (WxDxH)	m m	1250 x 560 x 1355		
External Dimension (WxDxH)	m m	1335 x 680 x 1985		
Packed Dimension (WxDxH)	m m	1420 x 750 x 2140		
40ft Container Load	pcs	25		