MKF 1021 S











Electric combi oven 10 trays 2/1 GN with electromechanic panel


With a three-knob electromechanical panel, the new MKF 1021 S oven allows high-performance management for achieving the best results in the kitchen with excellent, even cooking and fast times that result in reduced consumption, a characteristic that is the distinguishing mark of the entire MILLENNIAL line.














Pluc

Available on request at the order

Voltage (V): AC 220/230 3 PH

Left side opening door *

Adjustable door hinges

Equipment

Equipment	
Cardboard box dimensions with pallet (WxDxH mm)	910 x 1090 x 1295
Lateral supports	1 right + 1 left
Manual washing predisposition	
Condensate collection bowl, with drain on door	

Dimensional features

Dimensional features	
Dimensions (WxDxH mm)	850 x 1041 x 1130
Weight (kg)	140,4
Distance between rack rails (mm)	80

Hinge with door locking for openings adjusted at 60°, 90°, $1\overline{20}$ °, 180°

Optionals

Available in the dedicated section

Electrical features

Power supply (kW)	27,5
Frequency (Hz)	50/60
Voltage (V)	AC 380/400 3N
N° motors	3 bidirectionals
Boiler (kW)	/
Protection against water	IPX4

Functional features

Modularity

Functional features	
Power	Electricity
Capacity	N° 10 trays/grids 2/1 GN
Type of cooking	Ventilated
Steam	Direct steam controlled by knob (5 levels)
Cooking chamber	AISI 304 stainless steel
Temperature	100 - 270 °C
Temperature control	Thermostat
Control panel	Electromechanic - right side
N° programs	/
Programmable cooking steps	/
Pre-heating temperature	/
Pre-heating function	/
Door	Right side opening Ventilated Inspectionable glass

Yes

Adjustable