MKF 621 TS








Electric combi oven 6 trays 2/1 GN with TOUCH SCREEN














Dimensional features

| Dimensions (WxDxH mm) | 850 x 1035 x 850 |
|----------------------------------|------------------|
| Weight (kg) | 108,2 |
| Distance between rack rails (mm) | 80 |
| Electrical features | |
| Power supply (kW) | 18,4 |
| | |
| Frequency (Hz) | 50/6 |

| 50,00 |
|------------------|
| AC 380/400 3N |
| 2 bidirectionals |
| / |
| IPX5 |
| |

Functional features

| Power | Electricity |
|----------------------------|--|
| Capacity | 6 trays/grids 2/1 GN |
| Type of cooking | Semistatic + ventilated |
| Steam | Direct steam controlled by touch screen (10 levels) |
| Cooking chamber | AISI 304 stainless steel |
| Temperature | 30 - 270 ℃ |
| Temperature control | Digital probe thermometer |
| Control panel | Touch screen |
| N° programs | 500 |
| Programmable cooking steps | 10 |
| Pre-heating temperature | 180 ℃ |
| Pre-heating function | Programmable |
| Door | Right side opening Ventilated Inspectionable glass |
| Modularity | Yes |
| Feet | Adjustable |
| Optionals | |

| Optionals | |
|-----------------------------|------------------------------------|
| Condensation hood | MKKC 610 |
| Kit for a variancia a avera | MKS 64 |
| Kit for overlapping ovens | MKST 664 |
| Tables | MKTS 21 |
| | MKT 64 D |
| Other accessories | Available in the dedicated section |
| | |

| Cardboard box dimensions with pallet (WxDxH mm) | 910 x 1090 x 1015 mm |
|--|-------------------------------|
| Lateral supports | 1 right + 1 lef |
| USB port | |
| Multipoint core probe cod. MKSCMU/ | A |
| Support for core probe cod. MKSSC/A | |
| Automatic washing system integrated | l |
| Condensate collection bowl, with drai | n on door |
| Hinge with door locking for openings adju | usted at 60°, 90°, 120°, 180° |
| | |
| Plus | |
| Patented fan guard system Airflowlogic | TM |
| Patented system for direct steam Humil | ogic™ |
| Patented system for cooking chamber d | rying Drylogic™ |
| Available on request at the order — | Voltage (V) : AC 220/230 3 PH |
| | Left side opening doo |
| | Left side opening doo |
| Humidity management software | |
| · | |
| Humidity management software | |
| Humidity management software Wi-Fi communication system | |
| Humidity management software Wi-Fi communication system Knob for quick selection of the touch sc | |

(Iran), Philippine, Polish, Portuguese, Romanian, Russian, Serbian, Slovenian, South Korean, Spanish, Swedish, Thai, Turkish, Ukrainian,

Vietnamese HACCP system

Adjustable door hinges